



VARTA CR123A Battery

The VARTA CR123A from Pyronix is a 3.0V, $\geq 1.3\text{Ah}$ capacity lithium battery

A high-quality, yet cost-effective battery option for all your installation needs

- Pyronix approved battery for use on Pyronix security devices
- Boxes of 50
- Cost effective
- A quality CR123A battery that can be used across other devices

Reputable and reliable

A recognised and dependable battery from VARTA that ensures high standards and excellence with every battery fitted.

Fully tested for optimum performance

Although compatible with any device requiring a CR123A battery, these have been fully tested with relevant Pyronix products to ensure compatibility and peace of mind.

Suitable for any need

Providing long-life performance and suitable for a wide range of products.

Sold to suit

Available in packs of 50 from distributors and competitively priced, the VARTA CR123A from Pyronix helps keep your costs down whilst maintaining quality.

| BATT-VARTA-CR123A-R | |
|---------------------------|----|
| KX10DP-WE | ✓ |
| KX12DQ-WE | ✓ |
| KX15DC-WE | ✓ |
| KX12DT-WE | x2 |
| KX25LR-WE | ✓ |
| KX10DTP-WE | x2 |
| MC1 MINI-WE | ✓ |
| MC1/SHOCK-WE | ✓ |
| SMOKE-WE (2nd Generation) | ✓ |
| CO-WE (2nd Generation) | ✓ |
| HEAT-WE | ✓ |
| MCEXTERNAL-WE | ✓ |

| Specifications | |
|---------------------------------------|---------------------|
| Battery type | Lithium |
| Nominal voltage | 3VDC |
| Capacity | $\geq 1.3\text{Ah}$ |
| Dimensions ($\varnothing \times h$) | 16 x 34mm |
| Weight | 17g |
| Storage temperature | -20°C to 45°C |
| Discharge temperature | -40°C to 70°C |